

## Author Index Volume 47 (2015)

Afrand, M., see Mahmoodi, M.	(1)	21– 32
Agrawal, G.S., see Tiwari, D.K.	(2)	453– 465
Ahmed, S., see Ashraf, F.	(1)	237– 244
Akbari, M., see Mahmoodi, M.	(1)	21– 32
Alhawari, A.R.H., see Naeem, N.	(3)	827– 836
Alkanhal, M.A.S., see Ghaffar, A.	(3)	805– 817
Aneesh, M., see Singh, A.	(1)	163– 175
Ansari, J.A., see Singh, A.	(1)	163– 175
Ashraf, F., S. Ahmed, A.A. Syed and Q.A. Naqvi, Electromagnetic scattering from a topological insulator cylinder placed in chiral medium	(1)	237– 244
Ashraf, M.A., see Fiaz, M.A.	(1)	83– 93
Awasthi, M.K., see Tiwari, D.K.	(2)	453– 465
Bao, X., see Wang, H.	(2)	503– 512
Boumaiza, M. and D. Labeled, Lightning electromagnetic field coupling to overhead power distribution lines	(4)	1093–1106
Bu, Y., M. Nishiyama, T. Yamamoto and T. Mizuno, LLC resonance power transformers using magnetoplated wire	(3)	719– 727
Cai, H., see Li, P.	(1)	125– 139
Cao, Q., X. Han and L. Li, An active microfluidic mixer utilizing a hybrid gradient magnetic field	(3)	583– 592
Cardoso, M.P., see Silva, A.O.	(1)	113– 123
Chang, S., see Dai, J.	(2)	441– 451
Chawla, P. and R. Khanna, A new spiral frequency reconfigurable antenna with rf-mems switches for mobile RF front end	(2)	323– 335
Chen, I-F., see Shen, S.-M.	(4)	1085–1092
Chen, I-F., see Tsai, Y.-H.	(3)	653– 660
Chen, J., S. Huang and W. Zhao, Equivalent MFL model of pipelines for 3-D defect reconstruction using simulated annealing inversion procedure	(2)	551– 561
Chen, Q., see Cong, H.	(3)	737– 743
Chen, Q., see Zhu, H.-C.	(4)	927– 937
Chen, X., see Liu, Y.	(2)	433– 440
Chen, Y., see Fu, W.	(4)	875– 883
Chen, Z., see Guo, B.	(2)	411– 423
Cheng, C., see Guo, B.	(2)	411– 423
Cheng, J., see Xu, Z.	(3)	777– 790

- Cheng, S.-C., K.-C. Lee and C.-W. Huang, Radar target recognition by polarization-diversity RCS including random effects (4) 939– 949
- Coelho, M.A.E., Permanent magnet based magnetic levitation kit (4) 963– 973
- Cong, H., Q. Li, Q. Chen and J. Xing, Spatial dynamics modeling of the secondary arcs with power transmission lines (3) 737– 743
- Corte, A.D., see Giorgio, I. (4) 1051–1084
- Costa, J.C.W.A., see Silva, A.O. (1) 113– 123
- Courbon, J., see Uchimoto, T. (4) 993–1001
- Cui, X. and J. Hu, An infrasonic vibration energy harvester using pendulum impact (2) 467– 474
- Dai, F., see Yang, F. (3) 791– 804
- Dai, J., S. Chang and L. Liu, Optimization analysis of Electromagnetic Linear Actuator's radial array permanent magnets (2) 441– 451
- Dash, S.K., K.S. Swarup and K.K. Rajan, Design optimization of large gap single axis thrust magnetic bearing actuator (3) 661– 675
- Deegwal, J.K., see Sharma, M.M. (2) 523– 532
- Deng, F., see Xu, C. (1) 255– 262
- deng, Z., see Xu, C. (1) 255– 262
- Di Barba, P., M. Forzan and E. Sieni, Multiobjective design optimization of an induction heating device: A benchmark problem (4) 1003–1013
- Dincer, F., M. Karaaslan, E. Unal and C. Sabah, Design of tunable and dual/multi-band metamaterial based perfect microwave absorber (3) 729– 735
- Dong, R., see Zhou, Z. (4) 975– 991
- Douillard, T., see Uchimoto, T. (4) 993–1001
- Du, J., see Jiang, S. (1) 245– 253
- Duan, Z., see Ye, Z. (3) 847– 860
- Dwivedi, S., V. Mishra and Y.P. Kosta, Directivity enhancement of miniaturized microstrip patch antenna using metamaterial cover (2) 399– 409
- El-Bary, A.A., see Ezzat, M.A. (1) 95– 111
- El-Karamany, A.S., see Ezzat, M.A. (1) 95– 111
- El-Kharashi, E., Approaches to prove the rotor of the permanent magnet machine must be outside in order to improve the energy conversion process (1) 141– 152
- Esfe, M.H., see Mahmoodi, M. (1) 21– 32
- Ezzat, M.A., A.S. El-Karamany and A.A. El-Bary, Electro-magnetic waves in generalized thermo-viscoelasticity for different theories (1) 95– 111
- Fan, C., see Shi, J. (4) 951– 961
- Fan, F.-F., Z.-H. Yan and J.-H. Wang, A wideband 1:19 planar radial power divider design applied in circularly polarized array antenna (3) 819– 825
- Fan, L., see Yang, Y. (2) 425– 432
- Fang, J., see Peng, C. (3) 691– 704
- Fang, Y., see Wang, H. (2) 503– 512
- Fiaz, M.A. and M.A. Ashraf, On the investigation of scattered field from coated PEC cylinder buried beneath slightly rough surface (1) 83– 93

Forzan, M., see Di Barba, P.	(4)	1003–1013
Fu, G., see Zhang, Z.-Y.	(3)	745– 752
Fu, W. and Y. Chen, Data structures and program techniques of finite element methods for analysis and optimization of electric devices	(4)	875– 883
Galantucci, L., see Giorgio, I.	(4)	1051–1084
Gao, C.-F., see Meng, L.	(2)	337– 371
Gao, S., see Li, P.	(1)	125– 139
Ghaffar, A. and M.A.S. Alkanhal, Electromagnetic reflection and transmission from a planar isotropic chiral-uniaxial chiral interface with optical axis normal to interface	(3)	805– 817
Ghoggal, A., see Sahraoui, M.	(2)	483– 502
Giorgio, I., L. Galantucci, A.D. Corte and D.D. Vescovo, Piezo-electromechanical smart materials with distributed arrays of piezoelectric transducers: Current and upcoming applications	(4)	1051–1084
Giraldi, M.T.M.R., see Silva, A.O.	(1)	113– 123
Govil, M.C., see Sharma, M.M.	(2)	523– 532
Guedidi, S., see Sahraoui, M.	(2)	483– 502
Gulati, T., see Zhu, H.-C.	(4)	927– 937
Guo, B., Z. Chen, C. Cheng and Y. Yang, Characteristics of a nonlinear rotating piezoelectric energy harvester under variable rotating speeds	(2)	411– 423
Gupta, N., see Kumar, J.	(1)	263– 272
Gupta, N., see Sharma, A.K.	(1)	11– 19
Han, X., see Cao, Q.	(3)	583– 592
Han, Y., see Tang, E.	(2)	513– 521
He, L., see Tang, E.	(2)	513– 521
He, W., see Yang, F.	(3)	791– 804
He, Y., see Wang, H.	(2)	503– 512
Hong, T., see Zhu, H.-C.	(4)	927– 937
Hoole, P.R.P., S. Thirukumaran and S.R.H. Hoole, A software test-bed for electrical dynamics of direct cloud-to-ground and ground-to-cloud lightning flashes to aircraft: Initial results	(4)	911– 925
Hoole, S.R.H., see Hoole, P.R.P.	(4)	911– 925
Hoole, S.R.H., V.U. Karthik, S. Sivasuthan, A. Rahunanthan, R.S. Thyagarajan and P. Jayakumar, Finite elements, design optimization, and nondestructive evaluation: A review in magnetics, and future directions in GPU-based, element-by-element coupled optimization and NDE	(3)	607– 627
Hsue, C.-W., see Tsai, Y.-H.	(3)	653– 660
Hu, C., see Yang, W.	(3)	677– 689
Hu, C., Y. Sun, X. Lv, Z. Wang and Q. Xiong, Magnetic coupler design procedure for IPT system and its application to EVs' wireless charging	(3)	861– 873
Hu, J., see Cui, X.	(2)	467– 474
Huang, C.-W., see Cheng, S.-C.	(4)	939– 949
Huang, K., see Liu, Y.	(2)	433– 440

- Huang, K., see Yang, Y. (2) 425– 432
- Huang, K.-M., see Zhu, H.-C. (4) 927– 937
- Huang, S., see Chen, J. (2) 551– 561
- Huo, L., see Zhou, Y. (3) 629– 641
- Islam, M.M., see Samsuzzaman, M. (4) 1039–1049
- Islam, M.T., see Samsuzzaman, M. (4) 1039–1049
- Ismail, A., see Naeem, N. (3) 827– 836
- Jayakumar, P., see Hoole, S.R.H. (3) 607– 627
- Jayaraman, R., see Muthu, G.M. (1) 45– 59
- Ji, H., see Zhang, C. (4) 897– 909
- Jia, R., see Tian, L. (2) 293– 304
- Jiang, S. and J. Du, Theoretical analysis of a circular cylindrical piezoelectric trans-  
former with attached masses (1) 245– 253
- Jiao, Y.-C., see Zhang, Z. (2) 381– 387
- Jin, L., B. Lei, Z. Li and Q. Zhang, Dynamic response of rails due to armature  
movement for electromagnetic railguns (1) 75– 82
- Jung, K.S., A novel method transferring the copper rod without contact by axial  
magnet wheels (1) 187– 197
- Kamakshi, see Singh, A. (1) 163– 175
- Karaaslan, M., see Dincer, F. (3) 729– 735
- Karimipour, A., see Mahmoodi, M. (1) 21– 32
- Karthik, V.U., see Hoole, S.R.H. (3) 607– 627
- Khanna, R., see Chawla, P. (2) 323– 335
- Kim, T.H., Characteristic analysis of a flux-reversal motor driven by a four-switch  
converter with a compensated current regulation (1) 1– 9
- Klapka, M., see Strecker, Z. (2) 541– 550
- Kosta, Y.P., see Dwivedi, S. (2) 399– 409
- Kosta, Y.P., see Patel, A. (2) 563– 581
- Kumar, A., see Sharma, M.M. (2) 523– 532
- Kumar, J. and N. Gupta, Investigation on microwave dielectric materials for dielectric  
resonator antennas (1) 263– 272
- Kumar, J.V., see Muthu, G.M. (1) 45– 59
- Labed, D., see Boumaiza, M. (4) 1093–1106
- Lee, K.-C., see Cheng, S.-C. (4) 939– 949
- Lee, Y.-W., see Su, J.-P. (3) 593– 605
- Lei, B., see Jin, L. (1) 75– 82
- Li, C., see Shui, G. (4) 1023–1038
- Li, H., see Liu, S. (3) 705– 717
- Li, L., see Cao, Q. (3) 583– 592
- Li, L., see Zhao, W. (2) 373– 379

Li, P., S. Gao and H. Cai, Design, fabrication and performances of MEMS piezoelectric energy harvester	(1)	125– 139
Li, Q., see Cong, H.	(3)	737– 743
Li, S., see Wang, Y.	(2)	533– 539
Li, X., see Liu, S.	(3)	705– 717
Li, Z., see Jin, L.	(1)	75– 82
Lian, Z., see Liao, Y.	(1)	199– 209
Liao, Y., Z. Lian, R. Long and H. Yuan, Effects of multiple factors on the stress of the electro-hydraulic directional valve used on the hydraulic roof supports	(1)	199– 209
Lin, C.-H., Permanent magnet synchronous motor controlled V-belt continuously variable transmission driven electric scooter using hybrid modified recurrent Legendre NN control system	(1)	211– 235
Lin, D.-B., see Shen, S.-M.	(4)	1085–1092
Liu, C., see Liu, Y.	(2)	433– 440
Liu, D., see Zhou, G.	(3)	753– 764
Liu, G., see Zhou, Y.	(3)	629– 641
Liu, L., see Dai, J.	(2)	441– 451
Liu, S., see Tang, E.	(2)	513– 521
Liu, S., see Zhao, W.	(2)	373– 379
Liu, S., see Zhou, G.	(3)	753– 764
Liu, S., X. Li, S. Zhao and H. Li, Bifurcation and chaos analysis of a nonlinear electromechanical coupling transmission system driven by AC asynchronous motor	(3)	705– 717
Liu, X., see Yang, F.	(3)	791– 804
Liu, Y., X. Chen, G. Xu, C. Liu and K. Huang, A high gain and simple-structured dielectric resonator antenna array with cylindrical rods and microstrip feeding	(2)	433– 440
Liu, Z., see Wang, X.C.	(1)	177– 185
Long, R., see Liao, Y.	(1)	199– 209
Long, X., see Yu, X.	(2)	305– 312
Luo, R., see Wang, J.	(3)	837– 845
Luo, Y., see Yang, Y.	(2)	425– 432
Lv, Q., see Wang, H.	(2)	503– 512
Lv, X., see Hu, C.	(3)	861– 873
Ma, G., see Wang, Y.	(2)	389– 397
Mahdi, M.A., see Naeem, N.	(3)	827– 836
Mahmoodi, M., M.H. Esfe, M. Akbari, A. Karimipour and M. Afrand, Magneto-natural convection in square cavities with a source-sink pair on different walls	(1)	21– 32
Mandeep, J.S., see Samsuzzaman, M.	(4)	1039–1049
Mansor, F., see Samsuzzaman, M.	(4)	1039–1049
Masenelli-Varlot, K., see Uchimoto, T.	(4)	993–1001
Mazurek, I., see Strecker, Z.	(2)	541– 550
Meng, K., see Xu, Z.	(3)	777– 790
Meng, L. and C.-F. Gao, Electro-elastic fields around an elliptical hole in an electrostrictive plate: Isotropic and Uncoupled cases	(2)	337– 371
Ming, W., see Zhou, Y.	(3)	629– 641

- Mirsalim, M., see Yazdanpanah, R. (4) 885– 896
- Mishra, V., see Dwivedi, S. (2) 399– 409
- Mittal, K.C., see Reddy, C.S. (3) 643– 651
- Mizuno, T., see Bu, Y. (3) 719– 727
- Muthu, G.M., J.V. Kumar and R. Jayaraman, Computation and analysis of RCS for a kinetic energy type anti armour missile at Ka band (1) 45– 59
- Naeem, N., A. Ismail, A.R.H. Alhawari and M.A. Mahdi, Subwavelength negative index planar terahertz metamaterial arrays using spiral split ring resonators for near field sensing (3) 827– 836
- Naganuma, H., see Uchimoto, T. (4) 993–1001
- Nahar, M.K., see Samsuzzaman, M. (4) 1039–1049
- Naqvi, Q.A., see Ashraf, F. (1) 237– 244
- Nishiyama, M., see Bu, Y. (3) 719– 727
- Patel, A. and Y.P. Kosta, Multiple-band waveguide based band-stop filter (2) 563– 581
- Peng, C., J. Fang and C. Wang, Steering law for a cluster of magnetically suspended momentum wheels with vernier gimbaling capability (3) 691– 704
- Peng, C.-M., see Shen, S.-M. (4) 1085–1092
- Peng, L., see Xu, L. (2) 313– 322
- Qin, F., see Yang, W. (3) 677– 689
- Qiu, J., see Zhang, C. (4) 897– 909
- Rahunanthan, A., see Hoole, S.R.H. (3) 607– 627
- Rajan, K.K., see Dash, S.K. (3) 661– 675
- Reddy, C.S., A. Sharma and K.C. Mittal, Recovery analysis of spark gap by anode temperature decay method for different materials (3) 643– 651
- Roupec, J., see Strecker, Z. (2) 541– 550
- Sabah, C., see Dincer, F. (3) 729– 735
- Sahraoui, M., A. Ghoggal, S.E. Zouzou and S. Guedidi, Rotor fault detection algorithm based on a new fault indicator for induction motors fed from an industrial frequency inverter (2) 483– 502
- Samsuzzaman, M., M.T. Islam, M.K. Nahar, J.S. Mandeep, F. Mansor and M.M. Islam, Circularly polarized high gain S band antenna for nanosatellite (4) 1039–1049
- Sasaki, Y., see Uchimoto, T. (4) 993–1001
- Sayeed, S.S., see Singh, A. (1) 163– 175
- Shan, S., see Zhang, C. (4) 897– 909
- Shao, S., see Tang, M. (1) 33– 43
- Sharma, A., see Reddy, C.S. (3) 643– 651
- Sharma, A.K. and N. Gupta, An improved design of MEMS switch for radio frequency applications (1) 11– 19
- Sharma, M.M., J.K. Deegwal, M.C. Govil and A. Kumar, Compact printed ultra-wideband antenna with two notched stop bands for WiMAX and WLAN (2) 523– 532

Shen, S.-M., I-F. Chen, C.-M. Peng and D.-B. Lin, Analysis of multi-band operation of CPW feed monopole antenna by Gaussian filter model	(4)	1085–1092
Shi, J., C. Fan, M. Zhao and J. Yang, Variational analysis of thickness-shear vibrations of a quartz piezoelectric plate with two pairs of electrodes as an acoustic wave filter	(4)	951– 961
Shi, J.-M. and Z.-C. Yuan, Tunable filter using defect in one-dimensional plasma photonic crystals	(2)	475– 482
Shi, X., see Tang, E.	(2)	513– 521
Shui, G., C. Li and K. Yao, Non-destructive evaluation of the damage of ferromagnetic steel using metal magnetic memory and nonlinear ultrasonic method	(4)	1023–1038
Sieni, E., see Di Barba, P.	(4)	1003–1013
Silva, A.O., M.P. Cardoso, M.T.M.R. Giraldo and J.C.W.A. Costa, Investigation of the sensing properties of a localized surface plasmon nanocavity	(1)	113– 123
Singh, A., J.A. Ansari, Kamakshi, M. Aneesh and S.S. Sayeed, Analysis of slot loaded compact patch antennas for dualband operation	(1)	163– 175
Sivasuthan, S., see Hoole, S.R.H.	(3)	607– 627
Strecker, Z., J. Roupec, I. Mazurek and M. Klapka, Limiting factors of the response time of the magnetorheological damper	(2)	541– 550
Su, J.-P., J.-S. Wu and Y.-W. Lee, Use of electromagnetic induced flow fluctuations in a nanofluidic-assisted cooling device	(3)	593– 605
Su, L., see Ye, Z.	(3)	847– 860
Su, Y., see Ye, Z.	(3)	847– 860
Sugawara, K., see Uchimoto, T.	(4)	993–1001
Sun, Y., see Hu, C.	(3)	861– 873
Swarup, K.S., see Dash, S.K.	(3)	661– 675
Syed, A.A., see Ashraf, F.	(1)	237– 244
Takagi, T., see Uchimoto, T.	(4)	993–1001
Takahashi, Y., see Uchimoto, T.	(4)	993–1001
Takahata, K., see Ye, Z.	(3)	847– 860
Tan, Y., see Zhou, Z.	(4)	975– 991
Tang, E., X. Shi, Q. Zhang, M. Wang, D. Wang, S. Xiang, S. Liu, J. Xia, L. He and Y. Han, Characterization of light flash signatures using optical-fiber pyrometer detectors during hypervelocity impact	(2)	513– 521
Tang, M., H. Zou, H. Xu, S. Shao and C. Tian, Experimental investigation on electromagnetic transduction characteristic of linear oscillation electrical machine	(1)	33– 43
Thirukumaran, S., see Hoole, P.R.P.	(4)	911– 925
Thyagarajan, R.S., see Hoole, S.R.H.	(3)	607– 627
Tian, C., see Tang, M.	(1)	33– 43
Tian, L., Y. Tian, Q. Tian and R. Jia, Magnetic force analytic model of step conical PMB	(2)	293– 304
Tian, Q., see Tian, L.	(2)	293– 304
Tian, Y., see Tian, L.	(2)	293– 304

- Tiwari, D.K., M.K. Awasthi and G.S. Agrawal, Viscous potential flow analysis of electrohydrodynamic capillary instability with heat and mass transfer: Effect of free surface charge (2) 453– 465
- Tsai, Y.-H., C.-W. Hsue and I-F. Chen, Design of microwave active integrator using Z-transform technique (3) 653– 660
- Uchimoto, T., T. Takagi, Y. Takahashi, H. Naganuma, K. Sugawara, Y. Sasaki, T. Douillard, K. Masenelli-Varlot and J. Courbon, Thickness evaluation of thermally sprayed coatings after exposure to boiler tube environments by eddy current testing (4) 993–1001
- Unal, E., see Dincer, F. (3) 729– 735
- Vescovo, D.D., see Giorgio, I. (4) 1051–1084
- Wang, C., see Peng, C. (3) 691– 704
- Wang, D., see Tang, E. (2) 513– 521
- Wang, H., Q. Lv, Y. Fang, Y. He and X. Bao, Detection of air-gap eccentricity in induction machines using multi-position magnetic field measurement approach (2) 503– 512
- Wang, H., see Wang, Y. (2) 533– 539
- Wang, J., J. Yang and R. Luo, Non-contact transient high-voltage measurement with self-integrating D-dot probe (3) 837– 845
- Wang, J., see Zhang, Q. (1) 283– 291
- Wang, J., Y.-S. Xia and L.-Y. Wang, Electromagnetic responses of a metallic conical frustum cabin with one coaxial feeding monopole antenna (3) 765– 776
- Wang, J.-H., see Fan, F.-F. (3) 819– 825
- Wang, L.-Y., see Wang, J. (3) 765– 776
- Wang, M., see Tang, E. (2) 513– 521
- Wang, Q., see Wang, T. (1) 153– 162
- Wang, S.-C., see Zhang, Z.-Y. (3) 745– 752
- Wang, T. and Q. Wang, Coupling effects of a novel integrated electro-hydraulic energy conversion unit (1) 153– 162
- Wang, X.C., Z. Liu and Z. Zhou, Rapid computation model for accurate evaluation of electromagnetic interference shielding effectiveness of fabric with hole based on equivalent coefficient (1) 177– 185
- Wang, X.-M., see Zhang, Z. (2) 381– 387
- Wang, Y., G. Ma and C. Zhang, The wire traction microgripper design and experiments for stereo light microscope (2) 389– 397
- Wang, Y., S. Li, J. Yang, H. Zhou, H. Yi and H. Wang, Efficient solution to the RCS of trihedral corner reflector (2) 533– 539
- Wang, Z., see Hu, C. (3) 861– 873
- Weng, Z.-B., see Zhang, Z. (2) 381– 387
- Wu, J.-S., see Su, J.-P. (3) 593– 605
- Wu, L., see Zhu, H.-C. (4) 927– 937
- Wu, W.-J., see Zuo, S.-L. (4) 1015–1022



Xi, N. and J.-J. Yang, Optimal design of short-armature slotted type multi-segment permanent magnet linear synchronous motor for numerically controlled machine tool	(1)	273– 282
Xia, J., see Tang, E.	(2)	513– 521
Xia, Y.-S., see Wang, J.	(3)	765– 776
Xiang, S., see Tang, E.	(2)	513– 521
Xiao, C., see Zhou, G.	(3)	753– 764
Xing, J., see Cong, H.	(3)	737– 743
Xiong, Q., see Hu, C.	(3)	861– 873
Xiong, R., see Xu, C.	(1)	255– 262
Xu, C., Z. deng, R. Xiong and F. Deng, Time-step program for the sub-cell FDTD modeling of apertures with finite depth	(1)	255– 262
Xu, G., see Liu, Y.	(2)	433– 440
Xu, H., see Tang, M.	(1)	33– 43
Xu, L., F. Zheng and L. Peng, Electromechanical coupled nonlinear free vibration of rails for electromagnetic railguns	(2)	313– 322
Xu, R., see Zhao, W.	(2)	373– 379
Xu, Z., K. Meng and J. Cheng, Highly uniform single-sided portable NMR sensor and its application in assessing the aging level of silicone rubber insulators	(3)	777– 790
Yamamoto, T., see Bu, Y.	(3)	719– 727
Yan, Z.-H., see Fan, F.-F.	(3)	819– 825
Yang, B., see Zhang, Q.	(1)	283– 291
Yang, F., F. Dai, X. Liu, Y. Yang and W. He, Investigation on the magnetic bias current and electromagnetic force of power transformer in multi-layer soil area	(3)	791– 804
Yang, J., see Shi, J.	(4)	951– 961
Yang, J., see Wang, J.	(3)	837– 845
Yang, J., see Wang, Y.	(2)	533– 539
Yang, J.-J., see Xi, N.	(1)	273– 282
Yang, W., X. Zhao, C. Hu and F. Qin, The verification of force exerted on robotic capsule looped by magnet ring	(3)	677– 689
Yang, Y., H.Zhu, L. Fan, Y. Luo, F. Zhang and K. Huang, Broadband complex permittivity determination using a Two-port U-shaped coplanar waveguide with artificial neutral network algorithm	(2)	425– 432
Yang, Y., see Guo, B.	(2)	411– 423
Yang, Y., see Yang, F.	(3)	791– 804
Yao, K., see Shui, G.	(4)	1023–1038
Yazdanpanah, R. and M. Mirsalim, Analytical study of axial-flux hybrid excitation eddy current brakes	(4)	885– 896
Ye, Z., Z. Duan, L. Su, K. Takahata and Y. Su, Analysis of multi-direction low-frequency vibration energy harvester using diamagnetic levitation	(3)	847– 860
Yi, H., see Wang, Y.	(2)	533– 539
Yu, X. and X. Long, Parametric design of mechanical dither with bimorph piezoelectric actuator for ring laser gyroscope	(2)	305– 312
Yuan, H., see Liao, Y.	(1)	199– 209
Yuan, Z.-C., see Shi, J.-M.	(2)	475– 482

- Zhang, C., J. Qiu, H. Ji, S. Shan and J. Zhao, Damage localization using warped frequency transform in active structural health monitoring (4) 897– 909
- Zhang, C., see Wang, Y. (2) 389– 397
- Zhang, F., see Yang, Y. (2) 425– 432
- Zhang, Q., B. Zhou, B. Yang and J. Wang, An efficiency-improved hybrid implicit-explicit FDTD algorithm for analyzing electromagnetic scattering with fine geometries (1) 283– 291
- Zhang, Q., see Jin, L. (1) 75– 82
- Zhang, Q., see Tang, E. (2) 513– 521
- Zhang, Y., see Zhao, W. (2) 373– 379
- Zhang, Z., Y.-C. Jiao, Z.-B. Weng and X.-M. Wang, Compact dual-band bandpass filter using complementary hook-shaped resonators for WLAN applications (2) 381– 387
- Zhang, Z.-Y., S.-L. Zuo, J.-Y. Zhao, S.-C. Wang and G. Fu, Wideband bowtie antenna with inverted L-shaped coupling feed and tuning stubs for indoor base station applications (3) 745– 752
- Zhang, Z.-Y., see Zuo, S.-L. (4) 1015–1022
- Zhao, J., see Zhang, C. (4) 897– 909
- Zhao, J.-Y., see Zhang, Z.-Y. (3) 745– 752
- Zhao, M., see Shi, J. (4) 951– 961
- Zhao, S., see Liu, S. (3) 705– 717
- Zhao, W., see Chen, J. (2) 551– 561
- Zhao, W., Y. Zhang, L. Li, S. Liu and R. Xu, A W-band broadband single balanced mixer using an improved 180-degree hybrid (2) 373– 379
- Zhao, X., see Yang, W. (3) 677– 689
- Zheng, F., see Xu, L. (2) 313– 322
- Zhou, B., see Zhang, Q. (1) 283– 291
- Zhou, G., S. Liu, C. Xiao and D. Liu, Approach for a fast computation of induced magnetic field created by naval vessels (3) 753– 764
- Zhou, H., see Wang, Y. (2) 533– 539
- Zhou, R., see Zhou, Y. (3) 629– 641
- Zhou, Y., G. Liu, R. Zhou, L. Huo and W. Ming, Modeling and comparison of the Halbach array with different segments per pole (3) 629– 641
- Zhou, Z., see Wang, X.C. (1) 177– 185
- Zhou, Z., Y. Tan and R. Dong, Fault detection of piezoceramic actuator using non-smooth observer (4) 975– 991
- Zhu, H., see Yang, Y. (2) 425– 432
- Zhu, H.-C., L. Wu, T. Gulati, Q. Chen, T. Hong and K.-M. Huang, Bivariate characterization and measurement for effective permittivity of esterification reactions at 2450 MHz for multiphysics simulation (4) 927– 937
- Zou, H., see Tang, M. (1) 33– 43
- Zouzou, S.E., see Sahraoui, M. (2) 483– 502
- Zuo, S.-L., see Zhang, Z.-Y. (3) 745– 752
- Zuo, S.-L., Z.-Y. Zhang and W.-J. Wu, Wideband dual-polarized crossed bowtie dipole antenna with shorted stubs for base station applications (4) 1015–1022