

Author Index Volume 54 (2017)

- Abdel-Salam, N.M., see Ghaffar, A. (4) 489–499
Abrahamsson, J., see Hedlund, M. (3) 389–404
Abu-Nabah, B.A., Metallic coating thickness assessment over nonmagnetic metals using apparent eddy current conductivity spectroscopy (1) 77– 91
Ahmed, B., Z. Iqbal and E. Azhar, Combined effects of internal heat generation and mass effects on MHD Casson fluid with convective boundary conditions (2) 211–221
Akbaba, M., see Dalcali, A. (3) 341–350
Annasiwaththa, B.I., K. Oka and A. Harada, Magnetically levitated linear slider with a non-contact power transfer method (2) 223–237
Azhar, E., see Ahmed, B. (2) 211–221

Balassa, P., see Vértesy, G. (3) 449–459
Bao, X., C. Zhang, Y. Hu, Y. Chen and Z. Sheng, Combined passive shielding design of magnetic field generated by air-core reactor of power supply of EAST poloidal field (3) 289–299
Bernhoff, H., see Hedlund, M. (3) 389–404
Bu, W., Y. Huang, Z. Li, H. Shi and J. Shi, Diplacement sensorless control strategy of bearingless induction motor (4) 597–610

Cai, C., J. Wang, M. Hu, M. Long and Y. Zhou, Electromagnetic properties of cylinder permanent magnet eddy current coupling (4) 655–671
Cai, J., see Cao, Y. (1) 93–105
Cao, X., see Liu, Z. (2) 141–164
Cao, Y., S. Tao, J. Cai, L. Yu, H. Jia and Z. Tao, Magnetic field analytical solution and electromagnetic force calculation of coreless stator axial-flux permanent-magnet machines (1) 93–105
Chang, S., see Tan, C. (2) 199–209
Chen, C.-C., I-F. Chen, C.-M. Peng, C.-W. Hsue, Z.-H. Jiang and H.-Y. Liao, A novel multi-band broadband antenna for mobile handsets applications (1) 13– 22
Chen, I.-F., see Chen, C.-C. (1) 13– 22
Chen, L., see Li, X. (4) 611–626
Chen, L., see Li, X. (4) 647–654
Chen, R., see Li, X. (2) 239–248
Chen, R., see Li, X. (4) 553–567
Chen, R., see Li, X. (4) 611–626
Chen, R., see Li, X. (4) 647–654
Chen, R., see Ren, L. (2) 249–262

- Chen, X., Z. Deng, J. Hu and T. Deng, An analytical model of unbalanced magnetic pull for PMSM used in electric vehicle: Numerical and experimental validation (4) 583–596
- Chen, Y., see Bao, X. (3) 289–299
- Chen, Y., see Yan, J. (4) 515–524
- Cheng, X., H. Liu, S. Song, Y. Hu, B. Wang and Y. Li, Reconfiguration of tightly-coupled redundant supporting structure in active magnetic bearings under the failures of electromagnetic actuators (3) 421–432
- Cheng, X., see Tu, X. (1) 57– 76
- Cheng, Y., see Yu, Q. (1) 131–140
- Cheng, Y., see Yu, Q. (4) 501–514
- Chiariello, A.G., A. Formisano, F. Ledda, R. Martone and F. Pizzo, Analytical representation of 3D magnetic surfaces (4) 627–645
- Coufal, O., Faraday's law of electromagnetic induction in two parallel conductors (2) 263–280
- Dai, J., see Xu, S. (2) 177–186
- Dalcalı, A. and M. Akbaba, Comparison of the performance of bridge and bridgeless shaded pole induction motors using FEM (3) 341–350
- Deng, T., see Chen, X. (4) 583–596
- Deng, Z., see Chen, X. (4) 583–596
- Deng, Z., see Liu, Z. (2) 141–164
- Di Barba, P., B. Liu, M.E. Mognaschi, P. Venini and S. Wiak, Multiphysics field analysis and evolutionary optimization: Design of an electro-thermo-elastic microactuator (3) 433–448
- Ding, Z., see Ren, L. (2) 249–262
- Du, J., see Wang, X. (1) 37– 56
- Feng, Y., see Yan, J. (4) 515–524
- Formisano, A., see Chiariello, A.G. (4) 627–645
- Gao, P., see Wang, X. (1) 37– 56
- Gasparics, A., see Vértesy, G. (3) 449–459
- Ghaffar, A., M.M. Hussan, N.M. Abdel-Salam, K. Ibrahim, M.Y. Naz and Q.A. Naqvi, Echo width of plasma coated topological insulator cylinder (4) 489–499
- Guo, K., see Tang, E. (4) 569–581
- Han, B., see Ren, X. (4) 673–690
- Han, Y., see Tang, E. (4) 569–581
- Harada, A., see Annasiwaththa, B.I. (2) 223–237
- He, L., see Tang, E. (4) 569–581
- He, P., see Jiao, Z. (4) 535–551
- He, W., see Tang, B. (4) 461–470
- Hedlund, M., J. Abrahamsson, J.J. Pérez-Loya, J. Lundin and H. Bernhoff, Eddy currents in a passive magnetic axial thrust bearing for a flywheel energy storage system (3) 389–404
- Hsue, C.-W., see Chen, C.-C. (1) 13– 22
- Hu, J., H. Yi, Q. Yin, X. Zhou, R. Lu and Z. Ni, Design of a multilayer Halbach permanent magnet for human finger NMR detection (3) 315–327

- Hu, J., see Chen, X. (4) 583–596
 Hu, M., see Cai, C. (4) 655–671
 Hu, Y., see Bao, X. (3) 289–299
 Hu, Y., see Cheng, X. (3) 421–432
 Huang, S., see Zhang, Y. (3) 329–339
 Huang, Y., see Bu, W. (4) 597–610
 Hussan, M.M., see Ghaffar, A. (4) 489–499
- Ibrahim, K., see Ghaffar, A. (4) 489–499
 Iqbal, Z., see Ahmed, B. (2) 211–221
- Ji, J., see Zhang, X. (4) 525–534
 Jia, H., see Cao, Y. (1) 93–105
 Jia, S., see Tang, B. (4) 461–470
 Jiang, Z.-H., see Chen, C.-C. (1) 13– 22
 Jiao, Z., P. He, L. Yan, H. Liang and T. Wang, Hybrid thermal modeling of tubular linear oscillating motor based on sectionalized equivalent thermal circuit (4) 535–551
 Jiao, Z., see Yan, L. (3) 301–314
 Ju, P., see Ma, H. (2) 187–197
- Khan, S., see Ur Rehman, O. (1) 107–121
 Kim, S.-J., see Park, E.-J. (2) 281–288
 Kim, Y.-J., see Park, E.-J. (2) 281–288
- Le, Y., see Ren, X. (4) 673–690
 Ledda, F., see Chiariello, A.G. (4) 627–645
 Lei, G., see Li, Y. (1) 1– 12
 Li, X. and R. Chen, Quarter-wave short circuit in the application of lightning protection for signal transmission (2) 239–248
 Li, X., J. Zhang, R. Chen, L. Chen and Q. Xue, Analyses on the coordinated application of voltage switching type SPD and voltage limiting type SPD (4) 647–654
 Li, X., L. Chen, R. Chen, J. Zhang and Q. Xue, Analysis of the suppression method of lightning electromagnetic pulse coupled by receivers (4) 611–626
 Li, X., R. Zhu, R. Chen and J. Zhang, Coupling between over-head transmission lines and lightning electromagnetic fields (4) 553–567
 Li, Y., G. Lei, Y. Sun and L. Wang, Dynamics of magnetic suspension rotor system of turbo-expander (1) 1– 12
 Li, Y., see Cheng, X. (3) 421–432
 Li, Y., X. Zeng, L. Wei and Q. Wan, Characterizations of damage- induced magnetization for X80 pipeline steel by metal magnetic memory testing (1) 23– 35
 Li, Z., see Bu, W. (4) 597–610
 Li, Z., see Tang, E. (4) 569–581
 Li, Z., see Tang, E. (4) 569–581
 Liang, H., see Jiao, Z. (4) 535–551
 Liao, H.-Y., see Chen, C.-C. (1) 13– 22

- Liao, L., see Zhang, H. (1) 123–130
 Ling, Z., see Zhang, X. (4) 525–534
 Liu, B., see Di Barba, P. (3) 433–448
 Liu, C., see Liu, Z. (2) 141–164
 Liu, H., see Cheng, X. (3) 421–432
 Liu, J., see Ma, H. (2) 187–197
 Liu, L., see Tan, C. (2) 199–209
 Liu, S., see Tang, E. (4) 569–581
 Liu, Z., Z. Deng, Y. Yang, X. Cao and C. Liu, A switched reluctance motor with conical magnetic bearings (2) 141–164
 Long, M., see Cai, C. (4) 655–671
 Lu, Q., see Zeng, Z. (3) 351–366
 Lu, R., see Hu, J. (3) 315–327
 Lundin, J., see Hedlund, M. (3) 389–404
 Lv, H., see Wang, X. (1) 37–56
- Ma, H., J. Liu and P. Ju, Modeling and optimization of the maglev device for a vertical hydro-turbine (2) 187–197
 Mao, J., see Zhang, X. (4) 525–534
 Martone, R., see Chiariello, A.G. (4) 627–645
 Mészáros, I., see Vértesy, G. (3) 449–459
 Mognaschi, M.E., see Di Barba, P. (3) 433–448
 Mohamed, A., see Sarker, M.R. (4) 471–488
 Mohamed, R., see Sarker, M.R. (4) 471–488
- Naqvi, Q.A., see Ghaffar, A. (4) 489–499
 Naz, M.Y., see Ghaffar, A. (4) 489–499
 Ni, Z., see Hu, J. (3) 315–327
- Oka, K., see Annasiwaththa, B.I. (2) 223–237
- Park, E.-J., S.-J. Kim and Y.-J. Kim, Optimum design of salient magnetic gear with novel pole piece by central composite design (2) 281–288
 Peng, C.-M., see Chen, C.-C. (1) 13–22
 Pérez-Loya, J.J., see Hedlund, M. (3) 389–404
 Pizzo, F., see Chiariello, A.G. (4) 627–645
- Ren, L., R. Chen, H. Xia and Z. Ding, An omni-directional kinetic energy harvester using a novel spherical Halbach array transducer (2) 249–262
 Ren, X., Y. Le, B. Han and K. Wang, Loss optimization and thermal analysis of a heteropolar magnetic bearing for a vacuum turbo-molecular pump (4) 673–690
- Sarker, M.R., A. Mohamed and R. Mohamed, Implementation of non-controlled rectifier circuit based on vibration utilizing piezoelectric bending generator (4) 471–488
 Sheng, Z., see Bao, X. (3) 289–299

- Shi, H., see Bu, W. (4) 597–610
 Shi, J., see Bu, W. (4) 597–610
 Song, J., see Tang, E. (4) 569–581
 Song, S., see Cheng, X. (3) 421–432
 Sun, Y., see Li, Y. (1) 1– 12
- Tan, C., S. Chang and L. Liu, Dynamic performance design and analysis of hybrid excited linear actuator for on-off valve (2) 199–209
 Tang, B., W. He and S. Jia, A double-magnetic-source magnetic circuit with pole shoes for an electromagnetic angular vibration exciter (4) 461–470
 Tang, E., Z. Li, Q. Zhang, Y. Han, Z. Li, M. Wang, S. Xiang, S. Liu, L. He, J. Xia, K. Guo, H. Wang and J. Song, Experimental research on light flash generated by high-velocity impact on solar array (4) 569–581
 Tao, S., see Cao, Y. (1) 93–105
 Tao, Z., see Cao, Y. (1) 93–105
 Tian, L. and Q. Yu, Wide-speed-range sensorless control scheme for IPMSMs based on super-twisting observer and HF signal injection (3) 367–387
 Tomáš, I., see Vértesy, G. (3) 449–459
 Tu, X., R. Zhou, Y. Zhou and X. Cheng, Dynamical decoupling and feed-forward control for magnetically levitated planar actuators (1) 57– 76
- Ur Rehman, O., J. Yang, Q. Zhou, S. Yang and S. Khan, A modified QPSO algorithm applied to an engineering inverse problems in electromagnetics (1) 107–121
- Venini, P., see Di Barba, P. (3) 433–448
 Vértesy, G., P. Balassa, A. Gasparics, I. Tomáš and I. Mészáros, Inspection of diesel engine injectors by several electromagnetic nondestructive methods (3) 449–459
- Wan, Q., see Li, Y. (1) 23– 35
 Wang, B., see Cheng, X. (3) 421–432
 Wang, C., see Xu, S. (2) 177–186
 Wang, H., see Tang, E. (4) 569–581
 Wang, J., see Cai, C. (4) 655–671
 Wang, K., see Ren, X. (4) 673–690
 Wang, K., see Yan, B. (2) 165–175
 Wang, L., see Li, Y. (1) 1– 12
 Wang, M., see Tang, E. (4) 569–581
 Wang, Q., see Zhang, Y. (3) 329–339
 Wang, S., see Zhang, Y. (3) 329–339
 Wang, T., see Jiao, Z. (4) 535–551
 Wang, X., J. Du, P. Gao and H. Lv, Thermal comparison of a CFD analysis and a lumped parameter model of an air-cooled induction machine for EVs (1) 37– 56
 Wang, X., see Yu, Q. (1) 131–140
 Wang, X., see Yu, Q. (4) 501–514
 Wei, L., see Li, Y. (1) 23– 35

- Wiak, S., see Di Barba, P. (3) 433–448
- Wu, C., see Yan, B. (2) 165–175
- Xia, H., see Ren, L. (2) 249–262
- Xia, J., see Tang, E. (4) 569–581
- Xiang, S., see Tang, E. (4) 569–581
- Xie, N., Z. Zhang and C. Yin, Power losses and thermodynamic analysis of the solenoid fuel injector (3) 405–419
- Xu, S., C. Wang and J. Dai, Design and analysis of a vehicle magnetic particle clutch with permanent magnets (2) 177–186
- Xue, Q., see Li, X. (4) 611–626
- Xue, Q., see Li, X. (4) 647–654
- Yan, B., S. Zhang, X. Zhang, K. Wang and C. Wu, Self-powered electromagnetic energy harvesting for the low power consumption electronics: Design and experiment (2) 165–175
- Yan, J., K. Yang, S. Zhang, Y. Feng, Y. Chen and H. Yang, Comparative investigation of inset-type and V-type IPMSM for light electric vehicle (4) 515–524
- Yan, L., L. Zhang, Y. Zhao and Z. Jiao, Magnetic field and force output analysis of tubular linear machines with two structure topologies (3) 301–314
- Yan, L., see Jiao, Z. (4) 535–551
- Yang, H., see Yan, J. (4) 515–524
- Yang, J., see Ur Rehman, O. (1) 107–121
- Yang, K., see Yan, J. (4) 515–524
- Yang, M., see Zhang, H. (1) 123–130
- Yang, S., see Ur Rehman, O. (1) 107–121
- Yang, Y., see Liu, Z. (2) 141–164
- Ye, Y., see Zeng, Z. (3) 351–366
- Yi, H., see Hu, J. (3) 315–327
- Yin, C., see Xie, N. (3) 405–419
- Yin, Q., see Hu, J. (3) 315–327
- Yu, L., see Cao, Y. (1) 93–105
- Yu, Q., see Tian, L. (3) 367–387
- Yu, Q., X. Wang and Y. Cheng, Electromagnetic and thermal coupled analysis of can effect of a novel canned switched reluctance machine as a hydraulic pump drive (1) 131–140
- Yu, Q., X. Wang and Y. Cheng, Multiphysics optimization design flow with improved submodels for salient switched reluctance machines (4) 501–514
- Zeng, X., see Li, Y. (1) 23– 35
- Zeng, Z., Q. Lu and Y. Ye, Optimization design of E-core hybrid-excitation linear switched-flux permanent magnet machine (3) 351–366
- Zhang, C., see Bao, X. (3) 289–299
- Zhang, H., L. Liao, R. Zhao, J. Zhou, M. Yang and Y. Zhao, A new judging criterion for corrosion testing of reinforced concrete based on self-magnetic flux leakage (1) 123–130
- Zhang, J., see Li, X. (4) 553–567
- Zhang, J., see Li, X. (4) 611–626

- Zhang, J., see Li, X. (4) 647–654
Zhang, L., see Yan, L. (3) 301–314
Zhang, Q., see Tang, E. (4) 569–581
Zhang, S., see Yan, B. (2) 165–175
Zhang, S., see Yan, J. (4) 515–524
Zhang, X., see Yan, B. (2) 165–175
Zhang, X., W. Zhao, J. Ji, J. Zheng, Z. Ling and J. Mao, Influence of slot-pole configuration on reluctance torque in fractional-slot concentrated-winding interior permanent-magnet machines (4) 525–534
Zhang, Y., S. Huang, W. Zhao, S. Wang and Q. Wang, Electromagnetic ultrasonic guided wave long-term monitoring and data difference adaptive extraction method for buried oil-gas pipelines (3) 329–339
Zhang, Z., see Xie, N. (3) 405–419
Zhao, R., see Zhang, H. (1) 123–130
Zhao, W., see Zhang, X. (4) 525–534
Zhao, W., see Zhang, Y. (3) 329–339
Zhao, Y., see Yan, L. (3) 301–314
Zhao, Y., see Zhang, H. (1) 123–130
Zheng, J., see Zhang, X. (4) 525–534
Zhou, J., see Zhang, H. (1) 123–130
Zhou, Q., see Ur Rehman, O. (1) 107–121
Zhou, R., see Tu, X. (1) 57– 76
Zhou, X., see Hu, J. (3) 315–327
Zhou, Y., see Cai, C. (4) 655–671
Zhou, Y., see Tu, X. (1) 57– 76
Zhu, R., see Li, X. (4) 553–567